

Wall Mounted 9 and 12,000 BTU Systems

SYSTEMS 9R2, 12R2

	9R2		12R2	
	Heat Pump		Heat Pump	
Nominal Cooling <i>BTU/h</i>	9,700		12,300	
Nominal Heating <i>BTU/h</i>	9,600		12,800	
HSPF <i>BTU/hW</i>	8.2		8.2	
SEER <i>BTU/hW</i>	14.3		13.7	
EER <i>Clg/Htg</i>	11.8/13.9		11.5/12.9	
Clg. Operating Range °F(°C)	32~115 (0~46)		32~115 (0~46)	
Htg. Operating Range °F(°C)	17~75 (-8~24)		17~75 (-8~24)	
Moisture Removal <i>Pt./h(l/h)</i>	2.1 (1.0)		3.2 (1.5)	
Voltage/Frequency/Phase	115/60/1		115/60/1	
Recommended Fuse Size (A)	15		20	
Air Circ. <i>C.F.M. (m³/h)</i> : Hi	324 (550)		383 (650)	
Medium	271 (460)		324 (550)	
Low	241 (410)		265 (450)	
Quiet	200 (340)		206 (350)	
Noise Level <i>dB(A)</i> : Hi	40/38		45/42	
Medium	36/34		40/37	
Low	31/29		34/32	
Quiet	26/25		29/27	
Outdoor Fan Speed <i>RPM</i>	640		770	
Outdoor Noise Level <i>dB(A)</i>	43/45 (Clg/Htg)		45/46 (Clg/Htg)	
Current (A): Cooling	7.6		9.9	
Heating	6.5		9.2	
Power Use (kw): Cooling	0.82		1.07	
Heating	0.69		0.99	
Fan Speeds <i>Stage</i>	4 + Auto		4 + Auto	
Air Direction: <i>Horizontal</i>	Manual		Manual	
Vertical	Automatic		Automatic	
Air Filter	Washable		Washable	
Connection Method	Flare		Flare	
Combined Max. Lgth <i>Ft (m)</i>	49 (15)		49 (15)	
Max. Vertical Diff. <i>Ft (m)</i>	26 (8)		26 (8)	
Conn. Pipe Diameter <i>Inch</i>	Suc. 3/8	Dis. 1/4	Suc. 3/8	Dis. 1/4
Net Weight <i>lbs. (kg)</i>	21 (9.5)	71 (32)	21 (9.5)	79 (36)
Dimensions: Height <i>Inch</i>	10-13/16	21-3/8	10-13/16	21-3/8
<i>mm</i>	275	540	275	540
Width <i>Inch</i>	31-1/8	31-1/8	31-1/8	31-1/8
<i>mm</i>	790	790	790	790
Depth <i>Inch</i>	8-1/2	11-1/2	8-1/2	11-1/2
<i>mm</i>	215	290	215	290
Refrigerant	R410A		R410A	
	Indoor ASU9R2	Outdoor AOU9R2	Indoor ASU12R2	Outdoor AOU12R2

Note: Figures are based on 115 Volts.



Up to 14.3-SEER

Function

Stylish, slim and elegant, these popular wall mounted units are designed for single rooms. Indoor units have a clean, aesthetic design and are small but mighty and shorter in length than competing units, helping them blend into any room. 13 and 14-SEER heat pump systems have over a 30% increase in efficiency over conventional 10-SEER models and feature environmentally friendly R410A refrigerant, both heating and cooling operation, quiet mode and easy maintenance.

Standard Features

- Apple Catechin Filter
- Ion Deodorizing Filter
- Wireless Remote Control
- Sleep Timer
- 24-Hour Timer
- Dry Mode
- Auto Louver: Up/Down
- Auto Mode
- Quiet Mode
- Auto Restart/Reset
- Auto Changeover
- Low Ambient
- Cold Prevention

Easy Maintenance

Front panel is easily removed for cleaning.



Optional Remote

- ❑ Weekly Timer
- ❑ Full Function Wired Remote
- ❑ Child Lock Capable

UTY-RNBYU



Applications

This category of equipment is ideal for smaller spaces where spot cooling or heating is required. Residential applications including sunrooms and additions are made easier with these 115 volt air conditioners and heat pumps. Do you have a warm or cool spot in your home? Our mini-splits can provide extra cooling or heating capacity for those hard to cool areas. Commercially, their small size makes them ideal for small offices, providing individual temperature control.

