

Submittal Data: System 15RLS **ASU15RLS & AOU15RLS**



Job Name:		Location:	
Purchaser:			
Engineer:			
Submitted To:	For:	☐ Reference	☐ Approval
Submitted By:			
Unit Designation:	Schedule No.	Model No.:	

Capacities:

Cooling	14,5000 BTU/h
Outdoor Design Temp. <i>F° DB/WB</i>	95/75
Heating	18,000 BTU/h
Outdoor Design Temperature <i>F° DB/WB</i>	47/43
HSPF	11.0
SEER	21.0
EER <i>Cooling/Heating</i>	12.5/12.3
Voltage/Frequency/Phase	208-230/60/1

Indoor Unit:

Noise Level Cooling <i>db (A) - H/ M/ L/ Q</i>	46/ 40/ 33/ 25
Noise Level Heating <i>db (A) - H/ M/ L/ Q</i>	46/ 40/ 35 /26
Weight	18 lbs.

Outdoor Unit:

Noise Level <i>Cooling/Heating</i>	51/51
Recommended Fuse Size	20A
Min. Ampacity	10 A
Running Current <i>Cooling</i>	5.2A
Running Current <i>Heating</i>	6.4A
Weight	89 lbs.

Refrigerant Piping:

Max Ht. Difference	49 ft.
Max Total or Combined Length	66 ft.
Discharge Vapor Line (O.D.)	1/4 in.
Suction (O.D.)	3/8 in.

- | | | |
|-----------------------------------|---|---------------------------------|
| ♦ Seven year compressor warranty | ♦ Minimum Heat (50°F heating set point) | ♦ Optional Wired Remote Control |
| ♦ Five year parts warranty | ♦ Built in Low Ambient | ♦ Dry mode |
| ♦ Digital wireless remote control | ♦ Auto Restart/ Reset | ♦ Refrigerant R410A |
| ♦ 2-way automatic louvers | ♦ Sleep timer | ♦ Quiet Mode |

Notes:

OUTLINE AND DIMENSIONS

