

Submittal Data: System 18RLXS ASU18RLXS & AOU18RLXS



Job Name:		Location:		
Purchaser:				
Engineer:				
Submitted To:	For:	☐ Reference	☐ Approval	☐ Construction
Submitted By:				
Unit Designation:	Schedule No.	Model No.:		

Capacities:

Cooling	18,000 BTU/h
Outdoor Design Temp. <i>F° DB/WB</i>	95/75
Heating	21,600 BTU/h
Outdoor Design Temperature <i>F° DB/WB</i>	47/43
HSPF	10
SEER	19.2
EER <i>Cooling/Heating</i>	13.0/12.0
Voltage/Frequency/Phase	208-230/60/1

Indoor Unit:

Noise Level Cooling <i>db (A) - H/ M/ L/ Q</i>	43/ 37/ 33/ 28
Noise Level Heating <i>db (A) - H/ M/ L/ Q</i>	44/ 37/ 33/ 28
Weight	24 lbs.

Outdoor Unit:

Noise Level <i>Cooling/Heating</i>	47/50
Recommended Fuse Size	30A
Min. Ampacity	8.0A
Running Current <i>Cooling</i>	6.3A
Running Current <i>Heating</i>	8.0A
Weight	135 lbs.

Refrigerant Piping:

Max Ht. Difference	98 ft.
Max Total or Combined Length	164 ft.
Discharge Vapor Line (O.D.)	3/8 in.
Suction (O.D.)	5/8 in.

- | | | |
|-----------------------------------|------------------------------------|---------------------------------|
| ♦ Six year compressor warranty | ♦ Min Heat (50F heating set point) | ♦ Optional Wired Remote Control |
| ♦ Two year parts warranty | ♦ Built in Low Ambient | ♦ Dry mode |
| ♦ Digital wireless remote control | ♦ Auto Restart/ Reset | ♦ Refrigerant R410A |
| ♦ 4-way automatic louvers | ♦ 24 hour timer | ♦ Quiet Mode |

Notes:

OUTLINE AND DIMENSIONS

