


Job Name:	
Tag#	



Submittal Data Sheet	CDXS15LVJU
1.25-Ton Ducted Concealed Indoor Unit	



Complete warranty details available from your local dealer or at www.daikincomfort.com. To receive the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec. *If product is installed in a commercial application, limited warranty period is 5 years.*

Indoor Specifications				
	Cooling		Heating	
	H	M	H	M
Airflow Rate (cfm)	424	388	424	388
	L	SL	L	SL
	353	297	353	297
Sound (dBA) H / M / L / SL	37 / 35 / 33 / 31		37 / 35 / 33 / 31	
Dimensions (H x W x D) (in)	7-7/8 x 35-7/16 x 24-7/16			
Weight (Lbs)	60			
Nominal Capacity (Btu/hr)	15,000			


*See Outdoor Unit for Rated Capacities

Piping	
Liquid (in)	1/4
Gas (in)	1/2
Drain (in)	25/32

	Electrical	
	Cooling	Heating
Running Current (Rated) (A)	.79/.79*	.79/.79*
Power Consumption (Rated) (W)	172/172*	172/172*

*208/230V

CDXS15LVJU Dimensional Data



Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056


(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Optional Accessories



Included	Part Number	Description
	BRP072A43	Wireless Interface Adapter
	BRC944B2-A08	Wired Remote Controller
	BRCW901A08	Wired Remote Controller Cable – 25 ft (included in above kit)
	BRCW901A03	Wired Remote Controller Cable – 10ft
	DACA-ARCW901P10	IR Receiver Cable, Plenum Rated, 10ft (FDXS Only)
	DACA-ARCW901P25	IR Receiver Cable, Plenum Rated, 25ft (FDXS Only)
	DACA-CP2-1	Maxi Orange Condensate Pump
	DACA-CP3-1	Mini Condensate Pump 5 gph
	KRP928BB2S	Interface adaptor for DIII-NET
	KDT25N50	15, 18 Class Insulation kit for high humidity

External Static Pressure / Airflow Chart



Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)